

TRAILER PARTS & ACCESSORIES



FEATURES AND BENEFITS:

- Engineered for reliable and safe lift performance.
- Rust-resistant powder coat paint finish.
- Kits include industry-leading KTI pumps.
- Limited 3-year manufacturer's warranty.
- Kits come complete with hoist, hinges, KTI double-action pump, 110" hose, 120" hose, fittings, Bridon load control valve, prop kit (arm, cup and arm support) and battery cables.
- Patented Bridon load control valve lowers the dump box at a controlled speed whether the box is empty or overloaded in the event of a hose failure.



PART #	FINISH	PH / TONS	MAX FLOW RATE (GPM)	RELIEF PRESSURE (PSI)	BUTTON REMOTE	
PH516PHS-D122-P3	Black Powder Coat	516 / 8	2	3200	Υ	
PH520PHS-D122-P3	Black Powder Coat	520 / 10	2	3200	Υ	






IMPORTANT: Because of variations in application, the data contained in these tables is provided as a general guide only.

Capacities are based on the following:

- 1. Water level non-diminishing load.
- 2. The vertical height between the rear hinge pivot and the trailer floor is no less than 3 inches.
- 3. The hydraulic relief pressure is set at 3,200 psi.



PH516 Hoist Capacity (Tons)							
"A" Body (Feet)	"B" Overhang (Inches)	Dump Angle (Degrees)					
		45°	50°				
10	12	9.7	8.8				
10	18	11.1	10.0				
10	24	12.9	11.7				
12	12	7.7	7.0				
12	18	8.6	7.8				
12	24	9.7	8.8				
14	12	6.5	5.8				
14	18	7.0	6.4				
14	24	7.8	7.0				

PH520 Hoist Capacity (Tons)							
"A" Body (Feet)	"B" Overhang (Inches)	Dump Angle (Degrees)					
		45°	50°				
12	12	10.3	9.3				
12	18	11.4	10.4				
12	24	12.9	11.7				
14	12	8.6	7.8				
14	18	9.3	8.5				
14	24	10.3	9.3				
16	12	7.3	6.7				
16	18	7.9	7.2				
16	24	8.6	7.8				